

Topic 0


Software Architecture

Introduction - An Overview of Software Engineering Concepts and UML Modeling

Dr. Riad Sonbol


Outline of the course

- **The course covers the following core topics:**
 1. Introduction to Software Architecture and Its Importance.
 2. General Principles in Software Design and Architecture.
 3. Main Architectural Styles:
 - Layered Architecture (and N-Tier),
 - Client-Server Architecture,
 - MVC and its variations.
 - Ports and Adapter
 - Microservices
 - etc
 4. The Concept of Clean Architecture.
 5. Describing and Documenting Software Architecture Using UML.



Outline of the course

- **Textbooks:**
- *Ingeno, Joseph. Software Architect's Handbook. Packt Publishing Ltd, 2018.*
- *Martin, Robert C., Clean Architecture – A Craftsman's Guide to Software Structure and Design, Pearson , 2018.*




What do you know about Software Engineering?

- **Software engineering** is the branch of computer science that deals with the **design, development, testing, and maintenance of software applications**.
- Software engineering is the application of engineering principles to the development of software systems.
- What are the main SE Development Activities?

The Context: SE Development Activities

- 1) Requirements Elicitation.
 - 2) Analysis.
 - 3) System Design.
 - 4) Object Design.
 - 5) Implementation.
 - 6) Testing.
- Object-oriented software engineering is **iterative**; that is, activities can occur in parallel and more than once


*object-oriented software
engineering development
activities*



*object-oriented software
engineering development
activities*



In the last courses




Why is Design so Difficult?

Focuses on the
application domain

Focuses on the
solution domain

The solution domain is changing very rapidly

- *Halftime knowledge in SE $\approx$ 3-5 years*
- *Cost of hardware rapidly sinking*
- *Design knowledge is a moving target*




Modeling with UML- Quick Overview

What is modeling?


- the process of building an **abstraction** of reality.
- It involves creating a **simplified** representation that captures **essential** features of a system.
- The goal is to **make the complex reality more understandable, manageable, and analyzable.**

Significant to the problem at hand
i.e. depends on the purpose of the model

for different types of stakeholders




UML diagrams



Use Case Diagram


- Why use a UC diagram?
 - Represent interacts with people, organizations, or external systems
 - Represent the scope of your system
- Actors?
 - External objects that produce or consume data
 - a person, an organization, or an outside system



Use Case Diagram

- **There can be 5 relationship types in a use case diagram.**


- Association between actor and use case
- Generalization of an actor
- Extend between two use cases
- Include between two use cases
- Generalization of a use case



Use Case Diagram

■ Some Common Mistakes

- Extend vs Include?
- Generalize vs Extend?
- primary actor vs. secondary actor?



Use Case Description

Name: Purchase ticket

Participating actor: Passenger

Entry condition:

- Passenger standing in front of ticket distributor.
- Passenger has sufficient money to purchase ticket.

Exit condition:


- Passenger has ticket.

Event flow:


1. Passenger selects the number of zones to be traveled.
2. Distributor displays the amount due.
3. Passenger inserts money, of at least the amount due.
4. Distributor returns change.
5. Distributor issues ticket.

Exceptional cases!

UML diagrams



Class Diagrams




Class Diagrams

Class diagrams represent the structure of the system.

Used


- during requirements analysis to **model problem domain** concepts
- during system design to model **subsystems and interfaces**
- during object design to **model classes**.




Class Diagrams

A **class** represent a concept
Class = state (**attributes**) + behavior (**operations**)

Each attribute has a **type**.
Each operation has a **signature**.



Class Diagrams



Actor vs Class vs Instances?

An entity **outside**
the system


An abstraction modeling an
entity in the problem
domain **inside the system**

A specific instance
of a class

Association, Aggregation, and Composition

- **Association**(using relationship): The objects created and destroyed independently and represented as **one-to-one, one-to-many, or many-to-many** (also known as cardinality).
- **Aggregation**(HAS-A relationship): parent can exist without child and a child **can** exist independently of the parent
- **Composition**("death" relationship, PART-OF): parent destroyed, child dies

UML diagrams




UML sequence diagrams

■ Why UML Seq Diagram?


- To understand **the flow of control and data** between various elements in a system.
- **To identify the objects** involved in a particular scenario and the messages exchanged between them
- To find **additional objects** (“participating objects”)

■ System Sequence Diagram (SSD) vs Sequence Diagram


- A Sequence Diagram emphasizes the interactions between **objects within a system**, while a System Sequence Diagram (SSD) focuses on the interactions between **a system and its environment**




UML sequence diagrams




UML sequence diagrams



UML sequence diagrams



UML diagrams




State Chart Diagrams


Why UML State Diagram?

- Modeling the behavior of an interface, class, or collaboration.
- State diagrams emphasize the **event-ordered behavior of an object**, which is especially useful in modeling reactive systems.

Note that State is an Attribute or Collection of Attributes of object of type Incident




UML diagrams



Activity Diagram

- **Why Activity Diagram?**
 - Illustrate a business process or workflow between users and the system.
 - Simplify and improve any process by clarifying complicated use cases.
- **Note that State is an Operation!**
- **State chart diagrams** focus on the internal state of an object or system and how it responds to external events, while **activity diagrams** focus on the sequence of activities in a process or workflow



Other Modeling techniques!
*UML is not everything in
practical projects*


Diagram Elements

Flow Objects


Events



Activities



Gateways



Connectors

Sequence Flow



Message Flow



Association



Artifacts

Data Object



Name
[State]

Text Annotation




Add Text Here

Group




Swimlanes


Pool



Lanes (within a Pool)



Example



Case Study: ARENA

Description

- ARENA is a multi-user, Web-based system for organizing and conducting tournaments.
- ARENA is game independent in the sense that organizers can adapt a new game to the ARENA game interface, upload it to the ARENA server, and immediately announce and conduct tournaments with players and spectators located anywhere on the Internet.
- Organizers can also define new tournament styles, describing how players are mapped to a set of matches and how to compute an overall ranking of players by adding up their victories and losses (hence, figuring out who won the tournament).
- To recoup their operational costs, organizers can also invite potential sponsors to display advertisement banners during games.

Requirements Elicitation & Initial Analysis



How to Start a New Software Project!!

Description

Web-based system for organizing and conducting

main terms, entities, and concepts (glossary)?

ent in the sense that org
game to the ARENA game interface, upload it to the ARENA server, and immediately announce and conduct tournaments with players and spectators located anywhere on the Internet.

- Organizers can also define new tournament rules, how players are mapped to a set of matches and how to rank players by adding up their victories and losses (hence, figuring out who won the tournament)

Main actions, services, (use cases)

Main processes, flows, etc

- To recoup costs, organizers can also invite potential sponsors to display advertisement banners during games.

Good Starting Point

- ARENA is a multi-user, Web-based platform for organizing and conducting tournaments.
- ARENA is game independent. Organizers can adapt a new game to the ARENA game interface, upload it to the ARENA server, and immediately announce and conduct tournaments with players and spectators located worldwide.
- Organizers can also define new tournament styles, describing how players are mapped to a set of matches and how to compute an overall ranking of players by adding up their victories and losses (hence, figuring out who won the tournament).
- To recoup their operational costs, organizers can also invite potential sponsors to display advertisement banners during games.

Noun Phrases ≈ main concepts

Verbs ≈ Actions

Descript

You need more clarifications
from your client to understand
some terms

anners

- ARENA is a **multi-user, Web** organizing and conducting
- ARENA is **game** independent. **organizers** can adapt a new **game interface**, upload it to the ARENA **server**, and immediately announce and conduct **tournaments** with **players** and **spectators** located anywhere on the Internet.
- **Organizers** can also define new **tournament styles**, describing how **players** are mapped to a set of **matches** and how to compute an overall **ranking of players** by adding up their victories and losses (hence, figuring out who won **the tournament**).
- To recoup their **operational costs**, **organizers** can also invite **potential sponsors** to display **advertisement banners** during **games**.

Matches

multi-user web-based system

operational costs

Organizers

Players

potential sponsors

ranking of players

Server

Spectators

the tournament

tournament styles

New clarifications

→ Better Understanding

→ New possible Terms, actions, processes

■ ARENA is a multi-user system for organizing and conducting

■ ARENA is game interface where organizers can add new games, upload it to the ARENA server, and immediately conduct tournaments anywhere on the internet.

■ Organizers can describe how matches and of players by adding a tournament (hence, figuring out who won the tournament).

A Tournament is a series of Matches among a set of Players. Tournaments end with a single winner. The way Players accumulate points and Matches are scheduled is dictated by the League in which the Tournament is organized.

The TournamentStyle defines the number of Matches and their sequence for a given set of Players. For example, Players face all other Players in the Tournament exactly once in a round robin TournamentStyle.

Matches

multi-user web-based system

operational costs

Organizers

Players

potential sponsors

ranking of players

Server

Spectators

the tournament

tournament styles

Description

- ARENA is a **multi-user, Web-based system** for **organizing and conducting tournaments**
- ARENA is **game independent** in the sense that **organizers can adapt a new game to the game interface, upload it to the ARENA** and immediately **conduct tournaments** anywhere on the Internet
- **Organizers** can describe how **matches and of players** by adding **new players** (hence, figuring out who won **the tournament**)

*A League represents a community for running Tournaments. A League is associated with a specific Game and TournamentStyle. Players registered with the League accumulate points according to the **ExpertRating** defined in the League. For example, a novice chess League has a different ExpertRating formula than an expert League.*

*A Tournament is a series of Matches among a set of Players. Tournaments end with a single winner. The way players accumulate points and Matches are scheduled is dictated by **the League** in which the Tournament is organized.*

The TournamentStyle defines the number of Matches and their sequence for a given set of Players. For example, Players face all other Players in the Tournament exactly once in a round robin TournamentStyle.

operational costs
Organizers
Players
potential sponsors
ranking of players
Server
Spectators
the tournament
tournament styles

Finally!

Table 4-4 Working glossary for ARENA. Keeping track of important terms and their definitions ensures consistency in the specification and ensures that developers use the language of the client.

Game	A Game is a competition among a number of Players that is conducted according to a set of rules. In ARENA, the term Game refers to a piece of software that enforces the set of rules, tracks the progress of each Player, and decides the winner. For example, tic tac toe and chess are Games.
Match	A Match is a contest between two or more Players following the rules of a Game. The outcome of a Match can be a single winner and a set of losers or a tie (in which there are no winners or losers). Some Games may disallow ties.
Tournament	A Tournament is a series of Matches among a set of Players. Tournaments end with a single winner. The way Players accumulate points and Matches are scheduled is dictated by the League in which the Tournament is organized.
League	A League represents a community for running Tournaments. A League is associated with a specific Game and TournamentStyle. Players registered with the League accumulate points according to the ExpertRating defined in the League. For example, a novice chess League has a different ExpertRating formula than an expert League.
TournamentStyle	The TournamentStyle defines the number of Matches and their sequence for a given set of Players. For example, Players face all other Players in the Tournament exactly once in a round robin TournamentStyle.

Another Good Starting Point develop an example scenario

Des

rs

- ARENA is a **multi-user** organizing and conducting system.
- ARENA is **game** independent. **organizers** can adapt **game interface**, upload it to the ARENA **server**, and immediately announce and conduct **tournaments** with **players** and **spectators** located anywhere on the Internet.
- **Organizers** can also define new **tournament style** describing how **players** are mapped to a set of **matches** and how to compute an overall **ranking of players** by adding up their victories and losses (hence, figuring out who won **the tournament**).
- To recoup their **operational costs**, **organizers** can also invite **potential sponsors** to display **advertisement banners** during **games**.

Matches

multi-user web-based system

operational costs

Suggested Scenario

What if we want to launch a Chess Tournament? we understand better the client's expectation of the system, including the boundary of the system and the kinds of interactions between the user and the system

tournament styles

Requirements and High-Level Use Case Diagram

Description

- ARENA is a **multi-user, Web-based system** for organizing and conducting tournaments.
- ARENA is **game** independent in the sense that **organizers** can adapt a new **game** to the ARENA **game interface**, upload it to the ARENA **server**, and immediately announce and conduct **tournaments** with **players** and **spectators** located anywhere on the Internet.
- **Organizers** can also define new **tournament styles**, describing how **players** are mapped to a set of **matches** and how to compute an overall **ranking of players** by adding up their victories and losses (hence, figuring out who won **the tournament**).
- To recoup their **operational costs**, **organizers** can also invite **potential sponsors** to display **advertisement banners** during **games**.

advertisement banners

Game

Game interface

Matches

multi-user

operational costs

Organizers

Players

potential sponsors

ranking of players

Server

Spectators

the tournament

tournament styles

League



Actors:
Noun Phrases
Again!

Description

- ARENA is a **multi-user, Web-based system** for organizing and conducting tournaments.
- ARENA is **game** independent in the sense that **organizers** can adapt a new **game** to the ARENA **game interface**, upload it to the ARENA **server**, and immediately announce and conduct **tournaments** with **players** and **spectators** located anywhere on the Internet.
- **Organizers** can also define new **tournament styles**, describing how **players** are mapped to a set of **matches** and how to compute an overall **ranking of players** by adding up their victories and losses (hence, figuring out who won **the tournament**).
- To recoup their **operational costs**, **organizers** can also invite **potential sponsors** to display **advertisement banners** during **games**.

~~advertisement banners~~

~~Game~~

~~Game interface~~

~~Matches~~

Anonymous

~~multi-user~~

Admin

~~operational costs~~

~~Organizers~~

League owner

~~Players~~

Player

~~potential sponsors~~

advertiser

~~ranking of players~~

~~Server~~

~~Spectators~~


Spectators

~~the tournament~~

~~tournament styles~~

~~League~~

Till Now 😊



Description

- ARENA is a multi-user, Web-based system for organizing and conducting tournaments.
- ARENA is game independent in the sense that organizers can adapt a new game to the ARENA game interface, upload it to the ARENA server, and immediately announce and conduct tournaments with players and spectators located anywhere on the Internet.
- Organizers can also define new tournament styles, describing how players are mapped to a set of matches and how to compute an overall ranking of players by adding up their victories and losses (hence, figuring out who won the tournament).
- To recoup their operational costs, organizers can also invite potential sponsors to display advertisement banners during games.




Main services for each Actor

High Level
Functional
Requirements

- The **operator** should be able to **define** new games, **define** new tournament styles (e.g., knock-out tournaments, championships, best of series), **define** new expert rating formulas, and **manage** users.
- **League owners** should be able to **define** a new league, **organize** and announce new tournaments within a league, **conduct** a tournament, and **declare** a winner.
- **Players** should be able to **register** in an arena, **apply** for a league, **play** the matches that are assigned to the player, or **drop** out of the tournament.
- **Spectators** should be able to **monitor** any match in progress and **check** scores and statistics of past matches and players. Spectators do not need to register in an arena.
- **The advertiser** should be able to **upload** new advertisements, **select** an advertisement scheme (e.g., tournament sponsor, league sponsor), **check** balance due, and **cancel** advertisements.

High-level use cases



High-level use cases


Register	Anonymous users register with an Arena for a Player or a League-Owner account. User accounts are required before applying for a tournament or organizing a league. Spectators do not need accounts.
ManageUserAccounts	The Operator accepts registrations from LeagueOwners and for Players, cancels existing accounts, and interacts with users about extending their accounts.
ManageComponents	The Operator installs new games and defines new tournament styles
DefineLeague	The LeagueOwner defines a new league (
OrganizeTournament	The LeagueOwner creates and announces a new tournament, accepts player applications, schedules matches, and kicks off the tournament. During the tournament, players play matches and spectators follow matches. At the end of the tournament, players are credited with points
ManageAdvertisements	The Advertiser uploads banners and sponsors league or tournaments
ManageOwnProfile	The Players manage their subscriptions to mailing lists and answer a marketing survey.
BrowseTournamentHistory	Spectators examine tournament statistics and player statistics, and replay matches that have already been concluded (

Non-Functional Requirements

- **Low operating cost:** The operator must be able to install and administer an arena **without purchasing additional software** components and without the help of a full-time system administrator.
- **Extensibility:** The operator must be able to **add new games**, new tournament styles, and new expert rating formulas. Such additions may require the system to be temporarily shut down and new modules (e.g., Java classes) to be added to the system. However, no modifications of the existing system should be required.
- **Scalability:** The system must support the kick-off of **many parallel tournaments** (e.g., 10), each involving up to 64 players and several hundreds of simultaneous spectators.
- **Low-bandwidth network:** Players should be able to play matches via a 56K analog modem or faster.

Detailed Use Cases


High-level use cases




Use Case Specification

<i>Use case name</i>	OrganizeTournament
<i>Participating actors</i>	Initiated by LeagueOwner Communicates with Advertiser, Player, and Spectator
<i>Flow of events</i>	<ol style="list-style-type: none"> 1. The LeagueOwner creates a Tournament, solicits sponsorships from Advertisers, and announces the Tournament (include use case AnnounceTournament). 2. The Players apply for the Tournament (include use case ApplyForTournament). 3. The LeagueOwner processes the Player applications and assigns them to matches (include use case ProcessApplications). 4. The LeagueOwner kicks off the Tournament (include use case KickoffTournament). 5. The Players compete in the matches as scheduled and Spectators view the matches (include use case PlayMatch). 6. The LeagueOwner declares the winner and archives the Tournament (include use case ArchiveTournament).
<i>Entry condition</i>	<ul style="list-style-type: none"> • The LeagueOwner is logged into ARENA.
<i>Exit conditions</i>	<ul style="list-style-type: none"> • The LeagueOwner archived a new tournament in the ARENA archive and the winner has accumulated new points in the league, OR • The LeagueOwner cancelled the tournament and the players' standing in the league is unchanged.

Detailed use cases
refining the
OrganizeTournament
high-level use case.



Deeper



AdvertiserCreditExceeded

The system removes the Advertiser from the list of potential sponsors.

InvalidDate

The system informs the LeagueOwner and prompts for a new date.

MaxNumberOfTournamentsExceeded

The AnnounceTournament use case is terminated.


NameInUse

The system informs the LeagueOwner and prompts for a new name.

NoMatchingSponsorFound

The system skips the exclusive sponsor steps and chooses random advertisements from the advertisement pool.

The Big Picture



Identifying Entity Objects

a few simple heuristics
to distinguish between
noun phrases that
correspond to objects,
attributes, and
associations

- Attributes represent a single property of an object.

Flow of events

1. The **LeagueOwner** requests the creation of a **tournament**.
2. The system checks if the **LeagueOwner** has exceeded the **number of tournaments** in the **league** or in the **arena**. If not, the system presents the **LeagueOwner** with a form.
3. The **LeagueOwner** specifies a **name, application start and end dates** during which **Players** can apply to the tournament, **start and end dates** for conducting the tournament, and a **maximum number of Players**.
4. The system asks the **LeagueOwner** whether an exclusive sponsorship should be sought and, if yes, presents a **list of Advertisers** who expressed the desire to be **exclusive sponsors**.
5. If the **LeagueOwner** decides to seek an exclusive sponsor, he selects a subset of the **names of the proposed sponsors**.
6. The system notifies the selected sponsors about the upcoming tournament and the **flat fee** for exclusive sponsorships.
7. The system communicates their **answers** to the **LeagueOwner**.
8. If there are interested sponsors, the **LeagueOwner** selects one of them.
9. The system records the **name** of the exclusive sponsor and charges the flat fee for sponsorships to the **Advertiser's account**. From now on, all **advertisement banners** associated with the tournament are provided by the exclusive sponsor only.
10. If no sponsors were selected (either because no **Advertisers** were interested or the **LeagueOwner** did not select any), the advertisement banners are selected at random and charged to each **Advertiser's** account on a per unit basis.
11. Once the sponsorship issues is closed, the system prompts the **LeagueOwner** with a **list of groups of Players, Spectators, and Advertisers** that could be interested in the new tournament.

a few simple heuristics
to distinguish between
noun phrases that
correspond to objects,
attributes, and
associations

• Attributes have simple types.

• Complex concepts are
represented as objects that
are related to other objects
with associations.

Flow of events

1. The **LeagueOwner** requests the creation of a **tournament**.
2. The system checks if the **LeagueOwner** has exceeded the **number of tournaments** in the **league** or in the **arena**. If not, the system presents the **LeagueOwner** with a form.
3. The **LeagueOwner** specifies a **name, application start and end dates** during which **Players** can apply to the tournament, **start and end dates** for conducting the tournament, and a **maximum number of Players**.
4. The system asks the **LeagueOwner** whether an exclusive sponsorship should be sought and, if yes, presents a **list of Advertisers** who expressed the desire to be **exclusive sponsors**.
5. If the **LeagueOwner** decides to seek an exclusive sponsor, he selects a subset of the **names of the proposed sponsors**.
6. The system notifies the selected sponsors about the upcoming tournament and the **flat fee** for exclusive sponsorships.
7. The system communicates their **answers** to the **LeagueOwner**.
8. If there are interested sponsors, the **LeagueOwner** selects one of them.
9. The system records the **name of the exclusive sponsor** and charges the flat fee for sponsorships to the **Advertiser's account**. From now on, all **advertisement banners** associated with the tournament are provided by the exclusive sponsor only.
10. If no sponsors were selected (either because no **Advertisers** were interested or the **LeagueOwner** did not select any), the advertisement banners are selected at random and charged to each **Advertiser's** account on a per unit basis.
11. Once the sponsorship issues is closed, the system prompts the **LeagueOwner** with a **list of groups of Players, Spectators, and Advertisers** that could be interested in the new tournament.

Entity Object	Attributes & Associations	Definition
Account	<ul style="list-style-type: none"> balance history of charges (?) history of payments (?) 	An Account represents the amount currently owed by an Advertiser, a history of charges, and payments.
Advertiser	<ul style="list-style-type: none"> name leagues of interest for exclusive sponsorships (?) sponsored tournaments account 	Actor interested in displaying advertisement banners during the Matches.
Advertisement	<ul style="list-style-type: none"> associated game (?) 	Image provided by an Advertiser for display during matches.
Arena	<ul style="list-style-type: none"> max number of tournaments flat fee for sponsorships (?) leagues (<i>implied</i>) interest groups (<i>implied</i>) 	An instantiation of the ARENA system.
Game		A Game is a competition among a number of Players that is conducted according to a set of rules. In ARENA, the term Game refers to a piece of software that enforces the set of rules, tracks the progress of each Player, and decides the winner.
InterestGroup	<ul style="list-style-type: none"> list of players, spectators, or advertisers games and leagues of interests (<i>implied</i>) 	InterestGroups are lists of users in the ARENA which share an interest (e.g, for a game or a league). InterestGroups are used as mailing lists for notifying potential actors of new events.
League	<ul style="list-style-type: none"> max number of tournament game 	A League represents a community for running Tournaments. A League is associated with a specific Game and TournamentStyle. Players registered with the League accumulate points according to the ExpertRating of the League.

Entity Object	Attributes & Associations	Definition
LeagueOwner	<ul style="list-style-type: none"> name (<i>implied</i>) 	The actor creating a League and responsible for organizing Tournaments within the League.
Match	<ul style="list-style-type: none"> tournament players 	A Match is a contest between two or more Players within the scope of a Game. The outcome of a Match can be a single winner and a set of losers or a tie (in which there are no winners or losers). Some TournamentStyles may disallow ties.
Player	<ul style="list-style-type: none"> name (<i>implied</i>) 	
Tournament	<ul style="list-style-type: none"> name application start date application end date play start date play end date max number of players exclusive sponsor 	A Tournament is a series of Matches among a set of Players. Tournaments end with a single winner. The way Players accumulate points and Matches are scheduled is dictated by the League in which the Tournament is organized.

Identifying Boundary Objects


- Boundary objects represent the interface between the system and the actors. They are identified from the use cases and usually represent the user interface at a coarse level.

Boundary Object	Definition
TournamentForm	Form used by the LeagueOwner to specify the properties of a Tournament during creation or editing.
RequestSponsorshipForm	Form used by the LeagueOwner to request sponsorships from interested Advertisers.
SponsorshipRequest	Notice received by Advertisers requesting sponsorship.
SponsorshipReply	Notice received by LeagueOwner indicating whether an Advertiser wants the exclusive sponsorship of the tournament.
SelectExclusiveSponsorForm	Form used by the LeagueOwner to close the sponsorship issue.
NotifyInterestGroupsForm	Form used by the LeagueOwner to notify interested users.
InterestGroupNotice	Notice received by interested users about the creation of a new Tournament.


Identifying Control Objects

- Control objects represent the coordination among boundary and entity objects.
- In the common case, a single control object is created at the beginning of the use case and accumulates all the information needed to complete the use case, then destroyed with the completion of the use case
- Example:
 - **AnnounceTournamentControl**, which is responsible for sending and collecting notices to Advertisers, checking resource availability, and, finally, notifying interested users


Modeling Interactions Among Objects



UML sequence diagram for AnnounceTournament, tournament creation workflow.




UML sequence diagram for AnnounceTournament use case, sponsorship workflow



UML sequence diagram for AnnounceTournament use case, interest group workflow

Entity objects identified after analyzing the AnnounceTournament use case



Inheritance
hierarchy among
entity objects of
the
AnnounceTournamen
t use case

